

GRABEŽI GRAPPLES PINZE GREIFER



LIV

HIDRAVLIKA

izdelava hidravličnih žerjavov,
komponent in nadgradenj, d.o.o.
Postojna

Industrijska c.2
6230 Postojna
p.p. 77

Slovenija

tel.: +386 (0)5 728 38 71

fax.: +386 (0)5 728 39 05

<http://www.liv.si>

e-mail: liv@liv.si














TIP/TYP/TYPE/TIPO

GO 0,31

GO 0,42

GO 0,53

Površina prijemanja Greiffläche, Spitze-Spitze Gripping area, tip-tip Area di servizio max.	m ²		0,3	0,41	0,53
Najmanjši premer prijemanja Min. Greifdurchmesser Min. Gripping width Diametro min. di presa	m		0,12	0,12	0,15
Največja širina odprtih čeljusti Max. Greifweite Max. gripping width Massima apertura pinza	m		1,65	1,9	2,26
Višina pri odprtih čeljustih Höhe, bei max. Greifweite Height, max. Gripping width Altezza pinza aperta	m		0,75	0,88	0,93
Višina pri polodprtih čeljustih Höhe, Spitze-Spitze Height, tip-tip Altezza pinza punta/punta	m		0,91	1,08	1,16
Višina pri zaprtih čeljustih Höhe, geschlossen Height, closed Altezza pinza chiusa	m		0,57	0,64	0,69
Čas odpiranja pri pretoku 50 l/min Öffnungszeit bei 50 l/min Opening time at 50 l/min Tempo d'apertura (flusso 50 l/min)	s		2,1	2,1	2,4
Čas zapiranja pri pretoku 50 l/min Schliesszeit bei 50 l/min Closing time at 50 l/min Tempo di chiusura (flusso 50 l/min)	s		2,4	2,6	3
Sila stiskanja pri razmaku čeljusti 0,2 m Schliesskraft 0,2 m Abstand Gripping force 0,2 m Forza comprimente con le semi benne socchiuse di 0,2 m	kN		13,2	14,2	18,5
Širina pri zaprtih čeljustih Breite, geschlossen Width, closed Larghezza pinza chiusa	m		0,84	1,02	1,1
Širina Klammerbreite Width, grapple jaw Larghezza della semi benna	m		0,4	0,46	0,49
Največji obratovalni tlak Arbeitsdruck Operating pressure Pressione di esercizio	MPa		17,5	17,5	17,5
Nosilnost Tragfähigkeit Max. Load Portata max.	kN		30	40	55
Masa Masse Mass Peso	kg		175	235	340